

# Configuration files

Download file, copy it to microSD card (FAT/FAT32 filesystem), insert into display and go to Controller - Updates and settings - Import.

Don't change filename, or controller will not find it. If it was renamed by system (multiple files with same name) you need to fix filename.

Standard names for controller configurations: nconf.cfg, nconf2.cfg, ..., nconf9.cfg

## Small geared motors

Includes PID regulators preset for small geared motors.

[Import configuration 6](#)

## Sur-Ron Light Bee, 3 speed mode, configuration

Standard Sur-Ron configuration.

Default 16S battery (110A peak, 90A nominal), 500A phase, 48T wheel sprocket.

[Import configuration 3 for P24F](#)

[Import configuration 2 for older controllers](#)

Sur-Ron batteries specs:

32Ah ncr18650pf 110A max (11P) 6.6kW

34Ah ncr18650pf 110A max (11P) 6.6kW

38Ah Samsung 35e 88A max (11P) 5.3kW

40Ah NCR21700A 120A max (8P) 7.2kW

40Ah Greenway (year 2025+) 150A max 9.0kW

## Talaria Sting MX3, 3 speed mode, 8kW configuration

Talaria MX3 configuration.

Default 38.4Ah 16S battery, 500A phase, 13-44T sprockets.

[Import configuration 5](#)

MX3 battery specs:

Greenway. LG 21700 Li-Ion. 60V 38.4AH (2280 Wh). 135A 8.1kW

## Talaria Sting MX4, 3 speed mode, 11kW configuration

Talaria MX4 configuration.

Default 43.5Ah 16S battery, 500A phase, 13-44T sprockets.

You can setup up to 220A battery current at your own risk, this may damage battery!

[Import configuration 7](#)

## [Extract and import for SCUD battery \(130A continuous\)](#)

MX4 battery specs:

Greenway: LG 21700 Li-Ion. 60V 45Ah (2700 Wh) 180A 10.8kW

SCUD: LG 21700 Li-Ion 60V 45Ah (2700 Wh). 135A 8.1kW

N.B. some users reports that MX4 battery have about 2200wh usable.

MX5 battery specs:

Greenway: Samsung 50S cells. 72V 40Ah (2800 Wh) 210A 15.1kW

## Talaria Sting MX4, 30kW configuration

Talaria MX4 with Sotion fw02 motor

400a battery

320a field weakening

50a boost for 9 sec

80v 45ah zemso battery

Molicel p45 cells 500a bms

[Download and unzip](#)

## Talaria XXX, 3 speed mode, 6.6kW configuration

Talaria configuration.

Default 16S battery 110A 6.6kW, 400A phase, 14-48T sprockets.

[Import configuration 8](#)

## Apollo RFN, 3 speed mode, 12kW configuration

Apollo RFN configuration.

Default 20S battery 200A 12.0kW, 500A phase, 12-58T sprockets.

[Import configuration 4](#)

## E Ride SS Pro

[E Ride SS Pro 2.0 configuration.](#)

72V 40 Ah (2880Wh) 180A 13.0kW

E Ride SS Pro 3.0

72V 50 Ah (3600Wh) 230A 16.5kW

[Import configuration 9](#)

Setup your battery current in [Control modes] and in [Battery] menu after configuration import.

# 79bike Falcon Pro

79bike Falcon Pro configuration.  
72V 35 Ah (2520Wh). Tesing...

From:

<https://docs.nucular.tech/> - **Nucular Electronics**

Permanent link:

<https://docs.nucular.tech/doku.php?id=en:controller:config-files>

Last update: **2026/04/22 06:38**